

Nanoscale cathode materials for high power microbatteries

Tomás M. Clancy, Louise M. McGrath James F. Rohan


Electrochemical Materials and Energy, Tyndall National Institute, University College Cork, Lee Maltings, Ireland

1. Challenges facing energy sources for wireless sensors

The need for the integration of Li-ion batteries on chip results in space being at a premium.

Thin-Film (micron scale) solid-state batteries are an option for wireless sensors but they must overcome:

1. Low electronic conductivity.
2. Slow Li-ion diffusion.
3. Limited capacity.
4. Limited current capabilities.



Thin-Film Battery

$$\text{Diffusion Time} \sim \frac{(\text{Thickness (cm)})^2}{\text{Diffusion Coefficient (cm}^2\text{s}^{-1})}$$


2. Thin-Film vs. 3D Nanostructures

3D Nanostructures advantages:


- Reduce Li-ion diffusion length.
- Improve conductivity.
- Improve mechanical stability.

Results in:

- More uniform Li-ion distribution.
- Higher discharge rates can be reached.



Typical thin-Film Microbattery
If electrolyte conductivity 1 mS/cm



NanoCore-Shell
(ø200 nm Core, 250nm Shell)
If electrolyte conductivity 1 mS/cm

3. Results

35 and 100 nm DC sputter deposited nano-films of LiCoO₂.

Fastest theoretical charge and discharge time:

$$35 \text{ nm Diffusion Time} \sim \frac{(\text{Thickness (cm)})^2}{\text{Diffusion Coefficient (cm}^2\text{s}^{-1})} = \frac{(0.35 \times 10^{-5})^2}{2.0 \times 10^{-12}} = 6 \text{ s}$$



$$100 \text{ nm Diffusion Time} \sim \frac{(\text{Thickness (cm)})^2}{\text{Diffusion Coefficient (cm}^2\text{s}^{-1})} = \frac{(1.00 \times 10^{-5})^2}{2.0 \times 10^{-12}} = 50 \text{ s}$$

- LiCoO₂ Theoretical Capacity is 136.95 mAh/g

$$1 \text{ C} = 136.95 \text{ mA/g}$$



$$310 \text{ C} = 136.95 \times 310 = 42,454.5 \text{ mA/g}$$

$$310 \text{ C} = \frac{3600 \text{ (s)}}{310 \text{ (s)}} = 12 \text{ s}$$



Capacity of LiCoO₂ nano-films retained with cycling

LiCoO₂ cycled at high rate



High capacity achieved for LiCoO₂ even when cycling at high 310 C rate

Capacity only approaches 100 mAh/g for very high rate 200 C cycling (18 s charge and discharge)

Acknowledgments

- Science Foundation Ireland (SFI) Grant number: 12/IP/1722.
- SFI Connect Centre supported in part by a research grant from SFI co-funded by the European Regional Development Fund under Grant Number 13/RC/2077.