

Energy-autonomous systems based on thermoelectric energy harvesting:

- application-oriented system design and integration -

P. Woias, E. Bäumker, I. Schüle, A. Moser, M. Stegmaier, P. Mehne

Albert-Ludwigs-Universität Freiburg


Dept. of Microsystems Engineering (IMTEK)

Laboratory for Design of Microsystems

Freiburg, Germany

woias@imtek.de

Thermoelectric generators



Seebeck voltage

$$\Delta U = S \cdot \Delta T$$

output voltage


$$U_{out} = S \cdot \Delta T \cdot \frac{R_L}{R_{g,eff} + R_L}$$

output power

$$P_{out} = \frac{(S \cdot \Delta T)^2}{R_L} \cdot \left(\frac{R_L}{R_{g,eff} + R_L} \right)^2$$

Properties

- no moving parts
- DC-like currents, however...
- **polarity changes** with the direction of the temperature field
- very low to fair output voltages (10 mV ... V)



Maximum electrical output power

Example calculation for a mesoscale TEG

TEG: thermalforce™ TEG 049-150-30


- material system: Bi_2Te_3
- internal resistance: $R_{g,\text{eff}} = 0.57 \text{ Ohm}$
- Seebeck coefficient: $S = 16 \text{ mV/K}$
- dimensions: $25 \times 25 \times 3.7 \text{ mm}^3$

Assumptions

- temperature difference $\Delta T = 10\text{K}$
- ideal - and nonrealistic - thermal interface
- electrical load matching,
i.e. $R_L = R_{g,\text{eff}}$




$$P_{\text{out,ideal}} = \frac{1}{4} \cdot \frac{S^2}{R_{g,\text{eff}}} \cdot \Delta T^2 = 11.2 \text{ mW}$$



Thermal and electrical interfaces


Influence on output voltage and output power



$$U_{load} = \underbrace{\frac{R_{th,TEG}}{R_{th,TEG} + R_{th,h} + R_{th,c}}}_{\text{thermal interfaces}} \cdot \underbrace{S \cdot \frac{R_L}{R_{g,eff} + R_L}}_{\text{TEG electrical interface}} \cdot \Delta T$$

thermal interfaces **TEG** **electrical interface**

$$P_{el} = \left(\frac{R_{th,TEG}}{R_{th,TEG} + R_{th,h} + R_{th,c}} \right)^2 \cdot \frac{S^2}{R_L} \cdot \left(\frac{R_L}{R_{g,eff} + R_L} \right)^2 \cdot \Delta T^2$$



Thermal „feed factor“ f

- parameter for the thermal temperature divider at the TEG and its interfaces
- $0 < f < 1$: The higher f the better

$$f = \frac{R_{th,TEG}}{R_{th,TEG} + R_{th,h} + R_{th,c}}$$

Electrical „delivery factor“ d

- parameter for the electrical voltage divider at the TEG output
- $0 < d < 1$: For maximal power output $d_{opt} = 0.5$

$$d = \frac{R_L}{R_{g,eff} + R_L}$$

$$U_{out} = f \cdot d \cdot S \cdot \Delta T \quad \text{and} \quad P_{out} = f^2 \cdot d^2 \cdot \frac{S^2}{R_L} \cdot \Delta T^2$$

$$U_{out} \sim f \cdot d$$

$$P_{out} \sim f^2 \cdot d^2$$


Influence of the thermal interfaces

Practical example: TEG in a solid-air interface


Heat sink: Fischer ICK S

1.5 K/W ... 4.5 K/W

depending on air convection



TEG 049-150-30
5.263 K/W




Wacker P12 (50 μm thick)
2 x 0.1 K/W

Influence of the thermal interfaces

Example calculations

$$U_{Seebeck} = f \cdot S \cdot \Delta T$$

$$P_{max} = f^2 \cdot \frac{1}{4} \cdot \frac{S^2}{R_{g,eff}} \cdot \Delta T^2$$



| | acceptabe $\Delta T = 10K$ | | very low $\Delta T = 1K$ | |
|-----------------------------|----------------------------|----------------|--------------------------|----------------|
| | $U_{seebeck}$ [mV] | P_{max} [mW] | $U_{Seebeck}$ [mV] | P_{max} [mW] |
| low convection (0.5 m/s) | 83.9 | 3.1 | 8.39 | 0.031 |
| forced convection (4.5 m/s) | 121.8 | 6.5 | 12.18 | 0.065 |



Influence of the electrical interface

Output voltage and power for various load resistances and $\Delta T = 10K$

- low output voltage (10...100 mV)
- low-voltage step-up conversion **is mandatory**
- reasonable output power (mW...10 mW)

$$U_{out} = f \cdot d \cdot S \cdot \Delta T$$

$$P_{out} = f^2 \cdot d^2 \cdot \frac{S^2}{R_L} \cdot \Delta T^2$$





Influence of the electrical interface

Output voltage and power for various load resistances and $\Delta T = 1K$

- **very** low output voltage (mV...10mV)
- **very** low-voltage step-up conversion **is mandatory**
- **very** low output power (10 μ W...100 μ W)

$$U_{out} = f \cdot d \cdot S \cdot \Delta T$$

$$P_{out} = f^2 \cdot d^2 \cdot \frac{S^2}{R_L} \cdot \Delta T^2$$



Total system power output

$$P_{el} = \underbrace{\left(\frac{R_{th,TEG}}{R_{th,TEG} + R_{th,h} + R_{th,c}} \right)^2}_{f^2} \cdot \underbrace{\left(\frac{R_L}{R_{g,eff} + R_L} \right)^2}_{d^2} \cdot \frac{S^2}{R_L} \cdot \Delta T^2 \cdot \eta_{DC-DC}$$

Low output voltages (e.g. 100 mV) are not sufficient to power up an electronic system. A low-voltage step-up converter is required to boost the TEG output voltage up to an acceptable level (e.g. 2 V)

efficiency of an electronic step-up converter


Power losses in the step-up converter

- low efficiency at low input voltages (in many cases 25 % or less)
- minimum start-up voltage required (best commercial device: 20 mV in 2011)
 - ➡ *consequence:* No harvesting at „really low temperature gradients“


Low voltage (LV) step-up converters

Design issues


- high step-up ratio S
- high power conversion efficiency η
- **cold-start from low voltages** $U_{in, min}$
- self-supply from low input voltages
- **matched electrical impedances of TEG and converter input, for $d \sim 0.5$**



Power conversion efficiency of „usual“ low-voltage step-up converters



*datasheet Linear
Technology LTC 3108*





*N. V. Desai et al., Proc.
ISLPED 2014, 221-226*

Resume

- optimal power conversion only for a fixed input voltage V_{in} .
- not ideally suited for variable input voltage.
- minimal start-up voltage limited to 20 mV (today, with reasonable effort).

Our own LV step-up converter (patented)



P. Woias et al.,
J. Phys. Conf. Ser.
476, 2013, 012081.

Properties

- combination of a Meissner oscillator and forward converter
- start-up voltage of 10 mV is possible (reasonable: 20 mV)
- power conversion efficiency **above 50 % at 20 mV U_{in}** (most recent results)
- no influence of input voltage on conversion efficiency

Temperature regimes and design considerations

$$U_{out} = f \cdot d \cdot S \cdot \Delta T$$

Output power $\sim (\text{Seebeck} \cdot \Delta T)^2$ ←



$$P_{out} = f^2 \cdot d^2 \cdot \frac{S^2}{R_L} \cdot \Delta T^2$$

Resume

- **In general:** make output voltage U_{out} and output power P_{out} high enough, save on power in the electronic system
 - ➡ *high S = high-efficiency TEG*
 - ➡ *high f = thermal interfaces with good heat conductance*
 - ➡ *$d = 0.5$ (load-matched electrical interface) for max. power*
- **For a small ΔT :** use high-efficiency thermoelectric materials !
establish a ΔT as large as possible !
- **For a large ΔT :** even a „bad“ thermoelectric material may be sufficient !

Small ΔT applications

Human, biomedical, ...



© PMDM

Boundary conditions

- small ΔT : **one to a few Kelvin**
- small heat flux
- highly dynamic fluctuations of both

Home automation



Infrastructure monitoring

Small ΔT : Energy-autonomous sensors in railway and road tunnels

What for ?

- traffic monitoring
- environmental monitoring
- detection of accidents, explosions, earthquakes,...
- structural health monitoring



Available energies in a tunnel ?

| | railway tunnel | car tunnel |
|-----------|----------------|------------|
| thermal | ✗ | ✗ ✓ |
| sound | ✗ ✓ | ✗ ✓ |
| vibration | ✓ | ✗ |
| airflow | ✓ | ✓ |

Geothermal energy harvesting in tunnels?


Concept

- thermal probe embedded in the tunnel wall
- thermoelectric energy harvesting between the (cold ?) tunnel bed and the (warmer ?) wall surface


But first: measurement of the available ΔT

- temperature profile in the wall
- surface and air temperature
- wind speed

thermal probe with integrated thermogenerator (conceptual drawing)



Road tunnel: field measurements




Results

- predictable temperature profile in the wall
- highly dynamic air temperature
- influence of weather and traffic density
- **small temperature gradients (1...2 K)**

*Hugenwald tunnel,
Freiburg, Germany*

Thermal time constants




thermal time constant τ :



$$\tau = K_{HS} \cdot C_{HS}$$

$$P_{out} = P_{out}(t) \sim \underbrace{[\Delta T(t)]^2}$$


temporal behaviour of ΔT^2 does **also** define the output power



Energy harvesting from low ΔT in a tunnel



$$\tau = K_{HS} \cdot C_{HS}$$





$U = 20 \dots 60 \text{ mV}$

| TEG | $K_{HS} \text{ [K/W]}$ | $\tau \text{ [s]}$ | $E \text{ [J/day]}$ |
|-----|------------------------|--------------------|---------------------|
| 1 | 8.3 | 239 | 1.74 |
| 2 | 8.5 | 374 | 1.32 |
| 3 | 2.8 | 402 | 0.87 |
| 4 | 4.9 | 416 | 0.68 |

A. Moser et al., *Proc. PowerMEMS 2010*, Leuven, Belgium, 431-434.

Energy harvesting from low ΔT in a tunnel




Results

- harvesting of 0.07 J/day, from $\Delta T \geq 1.2 \text{ K}$ at the TEG over appr. 20 hrs
- 415 energy-autonomous radio telegrams per day (200 μJ per telegram, average interval: 3.5 min)
- wireless system: Enocean transmitter

A. Moser et al., *Journal of Electronic Materials* 41 (6), 2012, 1653-1661.

Wall-mountable modular sensor system



A. Moser et al., *Journal of Electronic Materials*
41 (6), **2012**, 1653-1661.

Medium ΔT applications

Fabrication



Boundary conditions

- acceptable ΔT : **at least 10s of Kelvin**
- reasonable heat flux
- moderate dynamics of both

Process control



© Citroen



© ABB

Automotive

Energy-autonomous sensors in automotive applications

What for ?

- tire pressure monitoring
- **engine monitoring and control**
(oil and water cycle, knocking...)
- tire rotation sensors ...

Available energies at/in a car or truck ?


- light
- movement
- acceleration
- **heat and cold**
- sound
- vibration
- gas and liquid flow




First measurement campaign: Thermal budgets in/around a car engine



Peugeot 306 (2000),
90 PS, gasoline




Miniaturized TEG module



TEG:
 $n \cdot \alpha = 4 \text{ mV/K}$
 $R_g = 0,21 \text{ Ohm}$



motor block

Pt 1000 (air temperature)



TEG module


Exemplary measurement results




Resume

- high output power (a few mW), but low output voltages (a few 10 mV)
- obvious influence of car speed
- significant harvesting **after** the end of a journey

Cold-start delay and conditions ?



12 mV--



Resume (for a small commercial TEG)

- 100 μ Ws of output power available after a few minutes
*a small TEG = sufficient for low-power wireless sensors **only***
- low-voltage step-up required “starting from as low as possible”
- higher output power required for realistic application scenarios

Second measurement campaign: A larger TEG in a modern car



datalogger

E




*Citroen C3 Picasso blueHDI 100
(2016), 100 PS, diesel engine*

TEG + heat sink

$n \cdot \alpha = 30 \text{ mV/K}$ $R_g = 0,89 \text{ Ohm}$

G



A: tip of oil level dip stick

B: cooling manifold

C: radiator support (top)

D: radiator support (bottom)



E: motor compartment air

G: exhaust surface temperature

H: chassis bottom (ambient air)

P. Mehne et al., *J. Phys.*
Conf. Ser. 773, **2016**, 012041.




Typical measurement results: Engine compartment



Results

- much lower temperatures in modern cars (2016) vs. elder cars (2000)
- substantial heat-up of the engine compartment at the end of a ride ➡ lower ΔT
- nevertheless potential for energy harvesting

Typical measurement results: TEG at the exhaust pipe



Results



- very high output power (up to 1 watt)
- significant start-up time (several minutes)
- requirements:

- *step-up converter with very low start-up voltage*
- *system electronics with low power draw (especially the wireless interface)*

load resistance at TEG:
 $R_L = 3.89 \text{ Ohm}$

Energy-autonomous temperature sensor at the exhaust pipe

System design and power consumption



| part | type | current | energy | power |
|------------------|-------------|---------------|-----------------|-----------------|
| start-up switch | MIC833 | 1 μ A | | $\sim 4 \mu$ W |
| microcontroller | MSP430F5529 | a few μ A | | $\sim 10 \mu$ W |
| bluetooth module | BLE112 | | 4.5 mJ/telegram | 4.5 mW |

Resume

- start-up at 20 mV input voltage (with an Enocean ECT 310 step-up converter)
- stable operation already with the car in idle mode
- however: further optimization required

P. Mehne et al., *J. Phys. Conf. Ser.* 773, **2016**, 012041.

High-temperature and ΔT applications

*Highly energetic
combustion processes*



Gas and aircraft turbines



Boundary conditions


- high temperatures: **100s of Kelvin**
- high ΔT : **100 to 100s of Kelvin**
- reasonable to high heat flux
- low dynamics of both (usually huge thermal masses involved)



High-power geothermy

High-temperature applications: a gadget example ?

BioLite 2[®] thermoelectric energy harvesting stove



Properties

- cold temperature level decreased via **active convective cooling**
- average electric power: 3 W
- integrated battery (2.600 mAh)

High-temperature applications: What TEGs are needed to power WSNs ?



$$P_{out} = f \cdot d \cdot \frac{S^2}{R_L} (T_2 - T_1)^2$$

➡ Output power ~ (Seebeck · ΔT)²

... but also: at least T₂ is high

Resume

- T is high
 - ➡ high-temperature thermoelectric materials required
 - ➡ a „bad“ thermoelectric material may be „good enough“
 - ➡ reduced requirements on system design (step-up converter)


Choice of thermoelectric materials

- high-temperature semiconducting thermoelectrics: *PbTe*, *SiGe*, *MgSi*,...
- **Why not metals ?**

High-temperature thermoelectric Materials

Why metal TEGs ?

- very small Seebeck coefficient ✗
- high operational temperature ✓
- very robust systems ✓
- raw materials readily available ✓




| | Typical Seebeck coefficient | Melting point |
|---|-----------------------------|---------------|
| Copper | 6.5 $\mu\text{V/K}$ | 1085 °C |
| Constantan ($\text{Cu}_{55}\text{Ni}_{45}$) | -35 $\mu\text{V/K}$ | 1280 °C |
| Bi_2Te_3 | $\sim 200 \mu\text{V/K}$ | 573 °C |
| PbTe | $\sim -100 \mu\text{V/K}$ | 905 °C |


Copper-constantan TEG: Theoretical case study

Device specification

- temperature difference at the TEG: 100K
- min. output power: ~100 mW
- thermal heat flux: ~100 Watt



| | |
|--|----------|
| Number of thermocouples | 241 |
| Seebeck coefficient (generator) | 10 mV/K |
| No load output voltage | 1.0 V |
| Loaded output voltage | 0.5 V |
| Max. output power | |
| too optimistic: $R_C = 0$ mOhm | 236 mW |
| realistic: $R_C = 1$ mOhm | 192 mW |
| Thermal heat flux through TEG | 100.78 W |



Summary and conclusions

Thermoelectric energy harvesting is promising – and feasible – for harvesting from thermal reservoirs with high and/or low heat fluxes and temperature differences.


In any case, a thorough system design is required, by tailoring

- the TEG itself, and its thermal interfaces,
- all power management electronics,
- the connected wireless sensor node.

Primary requirements and needs for further R&D are ...

- a realistic determination of energy densities available for harvesting,
- improved power management electronics,
- power-optimized wireless data transmission,
- a solution for the “low- ΔT -start-up”.

Thank you very much for your attention



Don't miss ...

PowerMEMS 2018, Daytona Beach, USA

- December 04-07, 2018
- abstract submission open
- deadline: July 17, 2018

Special session on:

“PowerMEMS in action”

... with working life demos

www.PowerMEMS.org

Peter Woias, EnerH

THE 18TH INTERNATIONAL CONFERENCE ON MICRO AND NANOTECHNOLOGY
FOR POWER GENERATION AND ENERGY CONVERSION APPLICATIONS

POWER MEMS

DAYTONA BEACH

FLORIDA, USA

DEC. 4-7 2018

CALL FOR PAPERS!

Abstract Submission Deadline – July 17, 2018

TOPICS

Focus Sessions

- Multiferroic Materials, Devices and Systems
- Energy for Wearables/Implantables
- Zero-Power Devices and Systems

General

- Energy conversion physics

Materials for Energy Conversion

- Materials for energy conversion and storage
- Energetic nanomaterials
- Fabrication technology for power/energy systems

Mechanical Energy Harvesting and Actuation

- Mechanical energy-harvesting
 - a-Electromagnetic b-Piezoelectric c-Electrostatic
 - d-Triboelectric e-Other
- Motors/generators, pumps and actuators

Direct Thermal Energy-Harvesting

- Thermal energy-harvesting
 - a-Thermoelectric b-Pyroelectric c-Others

Thermal and Chemical Science and Technologies for Power, Propulsion, and Cooling

- Fluid, heat and mass transfer and chemical reactions in power/energy systems
- Fuel cells, reactors, and combustors
- Thermal management, thermal logic, and nanoscale thermal effects
- Heat engines, coolers, and heaters
- Thrusters and propulsion systems

Electron, Ion, Photon and Radiation Energy Conversion

- Electron, ion and photon sources
- Photovoltaic and thermal photovoltaic cells
- Radioactive energy sources

Biochemical and Bio-Inspired Power/Energy Systems

- Biochemical and bio-inspired power/energy systems

Electrical Energy Harvesting, Management, Storage and Transfer

- Batteries, super-capacitors, and chemical energy storage
- Power electronics and energy management circuits
- RF, inductive and acoustic power transfer
- Electromagnetic energy harvesting

Applications and Innovations in Micro Energy Systems

- Power MEMS in Action – Demonstrations
 - a-Applications b-Devices and systems
 - c-Novel concepts and approaches
- Energy-autonomous wireless sensors for IoT
- Applications and market studies

PLENARY SPEAKERS

Veena Misra
North Carolina State University, USA

Roy (Troy) Olsson
Defense Advanced Research Projects Agency (DARPA), USA

Shashank Priya
Pennsylvania State University, USA

CONFERENCE CO-CHAIRS

David P. Arnold
University of Florida, USA

Luc G. Fréchette
Université de Sherbrooke, CANADA

TECHNICAL PROGRAM CHAIR

Florian Herrault
HRL Laboratories, USA

www.PowerMEMS.org

SPONSORED BY **TRF** TRANSDUCER RESEARCH FOUNDATION
connecting big ideas and small tech